

广州中逸光电子科技有限公司

测试报告 (Inspection report)

产品型号: SP15-S09				批号:			日期: 2014-06-20			仪器编号: LW2676;ADS1062C										
1. 耐压测试																				
Input to Output VAC Leakage current <u> 5 </u> mA at 1 min OK!																				
2. 测试数据																				
输入				输出																
U _{in} (VAc)		I _{in} (A)	P _{in} (W)	U _{out} (V)	I _{out} (A)	P _{out} (W)	效率 (η)	纹波噪声 (mV)	电压精度	电压调整率	负载调整率									
85	最小载	0.000	0.00	9.174	0.00	0.000			1.79%	0.02%	0.12%									
	半载	0.189	10.00	9.167	0.83	7.609	76.09%	43												
	满载	0.354	18.70	9.161	1.40	12.825	68.59%	150												
115	最小载	0.005	0.22	9.173	0.00	0.000						1.79%	0.02%	0.12%						
	半载	0.138	9.70	9.166	0.83	7.608	78.43%	42												
	满载	0.297	20.80	9.161	1.66	15.207	73.11%	86												
230	最小载	0.007	0.35	9.172	0.00	0.000									1.79%	0.02%	0.12%			
	半载	0.081	9.83	9.166	0.83	7.608	77.39%	44												
	满载	0.147	19.60	9.161	1.66	15.207	77.59%	46												
264	最小载	0.007	0.40	9.172	0.00	0.000												1.79%	0.02%	0.12%
	半载	0.075	9.84	9.166	0.83	7.608	77.31%	38												
	满载	0.134	19.60	9.159	1.66	15.204	77.57%	46												
									测试结果	符合技术手册参数要求 pass										
3. 稳定性																				
Vout	100%-0%-100%load					启动模式		turn on	测试结果	符合技术手册参数要求 pass										

测试		审核		批准	
----	--	----	--	----	--